



# Superflex

.....  
QUALITY  
.....



## Superflex Quality

è un film termosaldabile in poliuretano ecologicamente testato con superficie opaca antiriflesso, in conformità con l'Oeko-Tex Standard 100 classe 1.


Superflex Quality è adatto per il trasferimento su tessuti come cotone, miscele di poliestere/cotone e poliestere/acrilico. Può essere utilizzato per lettering su T-shirt, abiti per lo sport e il tempo libero, borse e articoli promozionali.

## Superflex Quality

is an ecologically proven polyurethane thermo adhesive with matt reflectionfree surface, in accordance with Oeko-Tex Standard 100 class 1.

Superflex Quality is suitable for transfer to textiles like cotton, mixtures of polyester/cotton and polyester/acrylic. Can be used for lettering on T-shirts, sport & leisure wear, sport bags and promotional articles.

SQ701.3 WHITE



SQ723.3 BORDEAUX



SQ730.3 MEDIUM YELLOW



SQ721.3 MAGENTA



SQ735.3 MILITARY GREEN



SQ702.3 BLACK



SQ731.3 YELLOW



SQ732.3 LEMON YELLOW



SQ727.3 BABY PINK



SQ719.3 ANTIQUE GOLD



SQ763.3 LIGHT BLUE



SQ703.3 GREY



SQ740.3 GOLD METALLIC



SQ728.3 FUCHSIA



SQ716.3 AUBERGINE



SQ737.3 GREEN



SQ707.3 TURQUOISE



SQ741.3 SILVER METALLIC



SQ760.3 SAPPHIRE



SQ722.3 CARDINAL RED



SQ704.3 NAVY BLUE



SQ715.3 PURPLE



SQ755.3 NEON YELLOW



SQ712.3 SKY BLUE



SQ724.3 FLAME RED



SQ705.3 ROYAL BLUE



SQ726.3 ORANGE



SQ754.3 NEON GREEN



SQ713.3 LILAC



SQ758.3 LIGHT GREEN



SQ738.3 FOREST GREEN



SQ717.3 BROWN



SQ752.3 NEON ORANGE



SQ735.3 APPLE GREEN




SQ711.3 ICE BLUE



SQ725.3 RED



SQ733.3 BEIGE



SQ753.3 NEON PINK



SQ708.3 AQUA GREEN



SQ720.3 VIOLET



## Lavorazione

Il Superflex Quality può essere intagliato con tutti gli attuali plotter da taglio. Si consiglia di utilizzare una lama standard a 45°. Dopo la spellicolatura il film può essere trasferito con una pressa a caldo. Il liner in poliestere deve essere rimosso quando ancora caldo. Successivamente si consiglia di pressare il materiale per altri 2 secondi con gli stessi parametri.

## Caratteristiche

Lavabile a 60° e adatto per il lavaggio a secco. Nylon e tessuti con impregnazione idrofobica non sono adatti per il trasferimento a caldo.

In questi casi si consiglia di utilizzare Superflex Quality. La garanzia di un fissaggio sicuro e duraturo di Superflex Quality è data solo rispettando la temperatura e la pressione specificata, si consiglia di fare prima un test su materiale di prova.

La morbida ed elastica pellicola offre una piacevole sensazione al tatto e un ottimo confort.

Superflex Quality ha un'eccellente opacità.

Le materie prime sono ecologicamente inerti, non contengono PVC, plastificanti o metalli pesanti (in conformità con l'Oeko-Tex Standard 100 classe I). Superflex Quality con il liner in poliestere autoadesivo, permette un riposizionamento dei motivi tagliati.

## Dimensioni standard

500mm x 25m

Altre dimensioni e colori speciali disponibili su richiesta.

## SUPERFLEX QUALITY

Film in poliestere / Polyester film

Adesivo sensibile alla pressione / Pressure sensitive adhesive

Film in poliuretano / Polyurethane film

Adesivo a caldo / Heat sealing adhesive

| Cotone<br>Cotton                       | misto cotone/poliestere<br>Cotton/polyester mixture | misto poliestere/acrilico<br>polyester/acrylic mixture |
|----------------------------------------|-----------------------------------------------------|--------------------------------------------------------|
| 155 - 165°C<br>17 - 20 sec.<br>3,5 bar | 155 - 165°C<br>17 - 20 sec.<br>3,5 bar              | 155 - 165°C<br>17 - 20 sec.<br>3,5 bar                 |

## Processing

Superflex Quality can be cut with all current plotters. We recommend to use a standard 45° knife. After weeding the cut flex film is transferred by heat press. The polyester liner should be removed warm. Afterwards we recommend pressing the material for another 2 seconds with the same parameters.

## Features

Washable at 60° and suitable for dry-cleaning. Nylon and textiles with hydrophobic impregnation are not suitable for heat transfer. In this case we recommend using Superflex Quality. Guarantee for a secure and long-lasting bond of Superflex Quality is only given when following the specified temperature and pressure conditions. We recommend evaluation on test material. The soft, elastic transfer film offers a comfortable textile touch and convinces due to high wearing comfort. Superflex Quality excels due to an excellent opacity. The raw materials are ecologically inert, do not contain PVC, plasticizer or heavy metals (in accordance with Oeko-Tex Standard 100 Class I). Superflex Quality with a self-adhesive polyester liner, enables a repositioning of cutted motives.

## Standard dimensions

500mm x 25m

Other dimensions and special colours available on request.



[www.superflex.biz](http://www.superflex.biz)  
[info@superflex.biz](mailto:info@superflex.biz)